



# Air Seeder GD 100



## DESIGNED & BUILT IN AUSTRALIA

- Fully welded & powder coated frame for maximum durability
- **Heavy duty 100mm RHS frame**
- Hydraulic drive variable rate control metering
- **Wide platform for safe and easy filling**
- Road legal transport widths
- **Semi-mounted 2 point hitch**

# GD 100 Series

## STANDARD FEATURES

- Arag Isobus Variable Rate Control
- Hydraulic Drive Metering System
- 50mm Nylon / Stainless Steel Metering Roller
- Road Transport Lighting & Signage
- Ground Following Wings with hydraulically Variable Down Pressure
- Powdercoated Frame & Bin
- Stainless Steel Manifolds
- Bin Cameras
- Large Toolbox
- 2 point Semi-mounted Hitch



## OPTIONAL FEATURES

- Farmscan 7500 Controller
- Small Seeds Box
- Brakes
- Fan Intake Heater
- Dual Wheels
- Load Cells

## SPECIFICATIONS \*

	GD 150	GD 160
Sowing Width	5.0m	6.0m
	16'5"	19'8"
Undercarriage	Graytill Double Disc Unit with side gauge wheel - Standard	
	Graytill Double Disc Unit with rear press wheel - Optional	
Disc Spacing	150mm (6") - Standard	
	100mm (4"), 125mm (5") - Optional	
Bin Capacity	1,500 Litres Front, 1,500 Litres Rear	
Wheels	500/60 - 22.5 16PR	
Number of Toolbars	2 Standard, 3 Optional	
Toolbar Spacing	1300mm - Standard	900mm - Optional
Drawbar Power Kw	105-135	120-150
Drawbar Power hp	140-180	160-200
Transport Width	3.47m	
Transport Height	3.4m	3.8m
Transport Length	7.6m	
Under Frame Clearance	350mm	

\*Specifications subject to change